

Product Datasheet

PM Wet Dash Finish



Hand Applied

1. About the Product

1.1 Composition

High Grade Silica Sand	BS EN 13139
Limestone	BS EN 13139
Cement	BS EN 197-1
Lime	BS EN 459-1
Additives	BS EN 934-2

Water added on site should be clean and free from any contaminants.

1.2 Uses

External Rendering

1.3 Application

Hand

1.4 Delivery

25kg Bags

1 Tonne Bags

1.5 Advantages of Stonepack Products

- Purity of materials ensure low co-efficient of shrinkage
- Minimal risk of cracking
- Water resistant and extremely durable
- Guaranteed total consistency of mix and colour
- Customer service and technical backup
- Low maintenance many years life expectancy
- Efficient prompt deliveries
- Excellent adhesion
- Excellent workability

2. Manufacture

2.1 Plant

All materials are batched and tested in the latest state of the art plant with constant testing at all stages of the process. The plant is capable of handling all sizes of order with complete quality assurance.

2.1 Samples

Small desk top size samples can be provided for colour identifications and 25kg sample bags will always be provided to ensure contract agreement.

3. Performance

This render should be applied to our traditional top coat which has to be applied 8-10mm thick. To allow good adhesion between the top coat & wet dash mix, a light key should be placed on the surface of the top coat. Once on site only clean water is required to be added & mixing with specially blended clean iron ore free aggregates will result in a well textured, easy to apply wet dash mix.

Water and aggregate addition on site must be measured and remain constant otherwise colour variance will occur. All new work must be protected from rain, sun and soiling during initial set.

For a complete uniformed colour we recommend using an exterior paint to finish.

4. On-Site

This company provides the full range of packaging for ease of site handling.

5. Coverage

Guideline only

Coverage (kg/m ²)
Approx 5

For all enquiries call us on 01307 462510
www.stonepack.co.uk

*Health & Safety Data is available on request and provided routinely with all deliveries.
Standard terms and conditions are provided with all quotations.*